

Axcys Wireless Alarm Contact

The Axcys wireless contact is part of the Axcys wireless Unit/Door alarm and monitoring system. It works by monitoring the position of a units roll up or swing door, detecting a change to its position. The wireless contact automatically sends a signal to the receiver of the change in door status prompting an alarm or alert depending on the circumstances. Mounted outside of units coupled with various possible mounting positions allow flexibility for easy installation either on rented or vacant units.



- Long range
- Easy Installation
- Mounts outside unit
- Roll Up or Swing Doors
- Uses 2 AA Industrial Batteries
- Long battery life

One System, Total Solution

Advanced automation for a secure self storage facility

FOR MORE INFORMATION, CONTACT:

www.axcys.com

Sales@global-electronics.com

800-591-6989

Technical Specifications



User Interface

Web Browser supported by Axcys Security Manager

Power supply

2 AA Industrial Alkaline Batteries (includeed)

Communication

433MHz International License Free band

Outputs

2 Dry Contact Relays with NO or NC Connections

Inputs

2 Magenetic Reed Switch

Interface

Over The Air (OTA) parameters user configurable

Maximum Quantity

Unlimited. (> 1 Million) May be broken in to 8 Zones and 16 groups

Available Software

Axcys Security Manager
Axcys Integrated

Adjustable

Alive notice
Address
Switch Use
Door check (default = 2 seconds)
Power output
LED Enable/Disable

Mechanical Properties

4.5" x 2.5" x 1.0"

FOR MORE INFORMATION, CONTACT:

www.axcys.com

Sales@global-electronics.com

800-591-6989